



# 3000 SERIES PRE-WIRED SOCKETS

**Product Data Sheet** 

Brooks' 3000 Series instrument transformer-rated meter sockets provide unmatched reliability and safety for transformerrated metering installations.

### **FEATURES**

- NEMA 3R, ANSI C12.7 & UL 414 compliant.
- 16-gauge G-90 galvanized steel.
- Munsell gray, powder coated, oven baked, high gloss finish.
- 0.80 aluminum with mill finish.
- Rating: 20 ampere, 600 volts AC, transformer-rated.

#### **APPLICATIONS**

Every socket we produce meets the unique requirements of each utility customer—down to the wire color code and test switch configuration. With more than 30 years of experience in supplying utilities with pre-wired meter sockets, you can trust Brooks to save you time & money.

## **DIMENSIONS**

- W 12" x H 19 7/8" x D 4 3/8"
- Six 3/4" x 1" x 1-1/4" knockouts bottom, sides, and back
- One 1/4" x 5/8" x 7/8" knockout—bottom







# PRE-WIRED METER SOCKET REQUEST

COMPANY:		CONTACT NAME:
ADDRESS:		PHONE #:
		E-MAIL:
INITIAL PURCHASE QTY:  1. MATERIAL:		ANNUAL USE QTY:
G90 Steel Aluminum (.080")		Standard Meter Socket Safety Meter Socket(Gray) Safety Meter Socket (Clear)
3. FINISH: Light Gray Powder Coat Padmount Green Powder Coat Mill Aluminum		Other
5. KNOCKOUTS:		Triplex 🔲
Standard $3/4$ " x 1" x 1-1/4"; (1 each	side, 1 back, 3 botto	m). 1/4" DIA-5/8" DIA-7/8" (1/2 KO, 1 EA bottom)
Other:		
6. HUB:  Blank	7. COVER: Ring Style (2 Piece) Ringless (1 Piece) Ringless (2 Pieces)	
9. WIRE SIZE: #10 #12 #14	<b>10. TYPE:</b> THHN Stranded THHN Solid	11. TEST SWITCH:  Number of Poles  Catalog #  None
*Attach copy of test switch specification	n, if available*	
<b>12. TEST SWITCH TYPE:</b> ☐ MOLDED BASE ☐ CUT BASE SIZE:		13. REVERSED POTENTIALS:  YES NO
14. WIRE HARNESS COLOR:		
<b>15. ASSEMBLY:</b> (P, N, C+, C-)		
14 HANDIE COLOR		
16. HANDLE COLOR:		
ICOLOP OPTIONS: BLACK B	LLIE RPOWN GRAV	GREEN, ORANGE, PURPLE, RED, WHITE, YELLOW)
Standard Test Switch Handle Colors (Cu Test Switch Handle Color To Match Wire	urrents=Black; Potentia	
17. PLATING:  NONE  TIN  NICKEL		18. HANDLES:  STANDARD  BI-COLORED



# PRE-WIRED METER SOCKET REQUEST

<b>19. STOPS:</b> ☐ NONE (STANDARD)  ☐ 60° ☐ 90°	20. COVER:    FRONT CONNECTED CLEAR   FRONT CONNECTED BLACK   COVER STUDS ONLY
21. CAPTIVE HARDWARE ON COVER?	22. BARRIERS:  SNAP-IN (STANDARD)  CHANNEL
23. TERMINAL TYPE:  #10 TERMINAL POST (STANDARD)  COMPRESSION (ST)	24. TEST EARS:  SERRATED (STANDARD)  OLD STYLE  BANANA JACK LINELOAD  NONE (STANDARD FOR ST SWITCHES)  ST
25. SPECIAL DETAILS:(SPECIAL MARKINGS, PACKAG	ING, GROUNDING, ETC.)

\*Return to Brooks CSR Email OR orders@brooksupg.com

