




# G SERIES BARREL LOCK & KEY PRODUCT DATA SHEET

#### **FEATURES**

- Barrel locks offered in three noninterchangeable combinations;
   G1, G2 and G3
- G1 and G2 series are constructed with hardened or stainless steel exterior lock bodies and stainless steel interior components
- \*G3 series are only available with stainless steel lock bodies and stainless steel interior components
- Thicker wall construction than conventional barrel locks provides exceptional durability and long service life
- Activated by special keys that are sold only to utilities
- Plunger O-ring prevents tampering by picking tools
- Field repairable version available



#### MODEL NUMBERS

G SERIES LOCKS	STAINLESS STEEL	HARDENED STEEL	DESCRIPTION
G1 852	4700	9700	Barrel lock without end cap
G2 853			'
*G3 854	4720	9710	Barrel lock with end cap

G SERIES KEYS	STANDARD KEY	REPAIRABLE KEY	REPAIRABLE KEY CARTRIDGE
G1	8615000	8615500	1527520
G2	8616000	8616500	1527522
G3	8617000	8617500	1527523

#### **PACKAGING**

Barrel Locks - 50 per box



### G SERIES BARREL LOCK & KEYS

#### **MAINTENANCE**

## The following User Tips will help you extend the life and performance of your Brooks Barrel Lock Key.

- The key is an instrument, not a tool. Rough handling or abuse can damage they key fingers and prevent them from mating with the barrel lock plunger.
- You will often sense an "click" when the fingers have properly engaged the barrel lock plunger. A slight turn of the handle will assure that proper engagement occurs.
- If a key fails to open the barrel lock the first time, remove the key and reinsert.
   DO NOT FORCE THE KEY OR JAM INTO THE LOCK. If you suspect the keyway is blocked, use a Brooks Barrel Lock Cleaning Tool to remove the dirt. Try the key again.
- Keep the protective cover on the key when not in use.
- Periodically inspect your key for worn or bent fingers. Clean the key with a toothbrush to remove dirt and other material that can collect on and under the key fingers.
- Do not use lubricant on keys or barrel locks. LPS-1, a non lubricating cleaner for electronics, is OK.
- Always install a plastic weather cap on the head of the barrel lock, or a plastic cap
  on the seal adapter to keep dirt and insects out of the barrel lock keyway.

#### **ACCESSORIES**



## Weather Cap Completely covers the lock head protecting it from water, dirt and debris



# Cleaning Tool Clears dirt and debris from a blocked keyway enabling better key function



Barrel Lock Puller Clamshell style puller grips tightly around the head to remove troubled locks