



LP with POTENTIAL

Product Data Sheet

Brooks' LP with Potential Adapters are low profile extender adapters with jaw blade connections only on specific line side locations.

FEATURES

- UL Listed, one-piece injection-molded polycarbonate interbase adapter.
- Lowest profile on the market at 1.2" depth.
- Clear dead-front safety shield.
- 11 jaw/blade locations with or without wire connection points.
- Provides safe, secure, and positive disconnection—no leakage and no hands inside the meter socket.
- Reusable long service life.
- Optional sealing ring available.

APPLICATIONS

Brooks' LP with Potential Adapters are used to disconnect a meter and leave it at the meter socket while providing potential on the line side in order to power meter electronics.

COLOR OPTIONS

RED



GREEN



GREY



MODEL NUMBERS

Meter Forms	Straight thru Jaw-Blade Positions	Red	Gray	Green
2, 12, 14, 15, 16, 17 & 25S	1, 3, 5, 7 & 9	LP-5J-SP4362 LP-5J-SP4570 (a)	LP-5J-SP4363 LP-5J-SP4571 (a)	LP-5J-SP4691 (a)
2S	1, 3	LP-2J-SP4364 LP-2J-SP4572 (a)	LP-2J-SP4365 LP-2J-SP4573 (a)	LP-2J-SP4679 (a)
2 & 12S	1, 3 & 5A	LP-3J-SP4634 LP-3J-SP4636 (a)	LP-3J-SP4637 (a)	
2, 12 & 25S	1, 3 & 5	LP-3J-SP4366 (**) LP-3J-SP4574 (**),(a)	LP-3J-SP4367 (**)	
		LP-3J-SP4576(**),(***),(a)		
2, 12 & 25S	1, 3, 5 & 5A	LP-4J-SP4368 LP-4J-SP4577 (a)	LP-4J-SP4369 LP-4J-SP4578 (a)	
14, 15, 16 & 17S	1, 3, 7 & 9	LP-4J-SP4372 LP-4J-SP4581 (a)	LP-4J-SP4582 (a)	LP-4J-SP4989

(**)- To change the 5th jaw/blade from pos. 5 to 5A by: 1) Remove the shield. 2) Remove the cotter pin from the 5th jaw/blade. 3) Move the jaw/blade. 4) Re-install the cotter pin & shield.

(***)- Without surge ground system.

(a)- Narrow blade required by some class 320 meter sockets in pos. #3 (upper right).